

Sup-R-Split Anchors

by MKT Fastening

Available Materials

- High strength, heat treated alloy steel, zinc plated
- Flat and duplex head
- Nickel rich electroplate for corrosive environments (Sup-R-Coat)

Features/Advantages

- Required hole diameter equals anchor diameter
- Friction set in solid masonry or stone
- High strength, heat treated alloy steel
- Corrosion-resistant (CR) for use in harsh climates or with ACQ lumber

Concerns

- Dead loads only

Approvals/Listings

- G.S.A. Spec FF-S-325C, Group VI



Cat No.	Description	Box Qty.	Box Wt. (lbs.)	Master Qty.	Master Wt. (lbs.)
Sup-R-Split Anchors					
1674060-	1/4" X 1-1/2" Flat Head	100	2.6	800	21
1674080-	1/4" X 2" Flat Head	100	3.1	800	25
1674100-	1/4" X 2-1/2" Flat Head	100	3.9	800	31
1674120-	1/4" X 3" Flat Head	100	4.4	800	35
1674140-	1/4" X 3-1/2" Flat Head	100	5.1	800	41
1674160-	1/4" X 4" Flat Head	100	5.8	800	46
1675110-	1/4" X 2-3/4" Duplex Head	100	3.6	500	30
1674120CR-	1/4" X 3" CR Flat Head	100	4.4	800	35
1674140CR-	1/4" X 3-1/2" CR Flat Head	100	5.1	800	41

Contact us today for a quote!

Hurripanel Fasteners



1.972.417.8882
or toll-free 1. 877.424.7616
www.hurripanel.com