Plastic Screw Anchor





Plastic Screw Anchor

Available materials

Polypropylene

Features/Advantages

- Light loads only under dead or slightly variable conditions in all atmospheric conditions
- Accepts both wood and sheet metal screws
- · Fast, easy installation




Order Detail

		Ultimate Tension in Lbs.* Screw Size Tested							
Order Code	Dia. & Length	Hole Dia.	Screw Size	8 x 1-1/4"	10 x 1-1/4"	10 x 1-1/2"	12 x 1-1/2	Box Qty.	Master Qty.
8450000	3/16" x 7/8"	3/16"	8-10	115	385	_	_	100	3,000
8451000	3/16" x 7/8"	3/16"	8-10	115	385	_	_	1,000	5,000
8460000	1/4" x 1"	1/4"	10-12	_	_	195	543	100	3,000
8461000	1/4" x 1"	1/4"	10-12	_	_	195	543	1,000	3,000
8430000	5/16" x 1-3/8"	5/16"	14-16	n/a	n/a	n/a	n/a	100	1,200
Kits With Drill And Screws									
**8450100	3/16" x 7/8"	3/16"	8	115	385	_	_	1	12
**8460100	1/4" x 1"	1/4"	10			195	543	1	12

^{*}Tested in concrete block.

Installation

- 1 Drill recommended diameter hole slightly deeper than length of anchor.
- 2 Clean hole of debris.
- 3 Insert plastic anchor into hole.
- 4 Place fixture over anchor and insert screw through fixture and into anchor.
- 5 Tighten screw.



^{**}Includes Carbide Drill Bit and 100 Anchors and Screws